

Factory Add: Taiwanese Investment Park, Quanzhou, Fujian Province, China. **Web Site:** www.socmachinery.com

TEL: +86-592-5650662

Fax: +86-592-5650876

E-mail: alex@socmachinery.com.cn

Specification Forklift HNF350

Model	HNF350		Unit	
Performance	Load capacity		kg	35000
	Load center		mm	1250
	Maximum fork height		mm	3500
	Lifting speed(wz/wo load)		mm/s	250/260
	Mast tilt angle (forward/backward)		°	6/12
	Max. Travel speed (full load/without load)		kmh	25/28
	Turning radius(outside)		mm	7260
	Grade ability (wz/wo load)		%	20/20
Dimension	Overall length (wz/wo fork)		mm	9700/7150
	Fork size (L*W*T)		mm	2440*340*125
	Overall width		mm	3320
	Width of fork carriage		mm	2700
	Overall height	mast lowed	mm	4010
		overhead guard	mm	3860
	Wheelbase		mm	4800
	Ground clearance (wz load)	wheelbase center	mm	460
		mast lowered point	mm	400
Weight	Total weight		kg	43000
Tire	Tire numbers & size Front			4*16.00-25/32PR
	Tire numbers & size Rear			2*16.00-25/32PR
	Wheel tread	Front	mm	2400
		Rear	mm	2450
Brake	Service	Air over Hydraulic clamp disc brake		
	Parking	Spring press clamp disc brake		
Transmission	Manufacturer /Type	ZHONGNAN/ Automatic power-shift		
	Number of speed	Forward2/Reverse1		
Engine Diesel	Option 1.	Manufacturer/Model	WEICHAi	WP10G240E341
		Rated power/rotate speed	kw/r.pm	178/2200
	Option 2.	Manufacturer/Model	CUMMINS	QSB8.3-C260
		Rated power/rotate speed	kw/r.pm	194/2200
Top lifting Spreader	Suit for 40 feet container lifting, mounting on fork, hydraulic control, removable			







